


HydroLink™ Watering System



Battery Watering Made Easy

Proper maintenance and periodic watering are important factors in maximizing the performance and life of Trojan deep-cycle, flooded batteries. Battery maintenance can be a costly, time-consuming and messy job. With Trojan's HydroLink™ advanced, single-point watering system, precise battery watering is made easy saving valuable time and money.

Independent Water Level Indicator



Water Indicator Signal



Snake™ Tubing



Clampless Tubing



Coupler Connection with Water Flow Indicator



Convenient Installation

Trojan's HydroLink watering system is specifically designed to work with Trojan 6-volt and 12-volt flooded batteries* and takes the guess work out of properly watering flooded batteries. With a simple installation of the HydroLink manifolds and the tubing, the system is ready for use. Once installed, a complete set of batteries can be filled in less than 30 seconds.

HydroLink™ Vent

The HydroLink™ vent assembly is unique and features an independent water level indicator, valve shut off and dual flame arrestors.

Independent Water Level Indicator

Maintaining the proper electrolyte level can extend the performance and life of Trojan flooded batteries. However, determining the correct level can be a challenge. Trojan's HydroLink vent features an independent water level indicator that accurately displays whether a battery needs watering. A white indicator signals that the battery needs water. A black indicator signals that the battery has enough water...it's that simple.

Valve Shut Off

The valve shut off accurately controls cell electrolyte levels. Using a balanced valve design, the shut off valves automatically cut the water flow into the individual cells eliminating the potential of overflow or acid splash caused by overfilling. HydroLink's valve shut off works in conjunction with the hose end assembly and flow indicator to provide precise battery watering.

Dual Flame Arrestors

The HydroLink system is equipped with dual flame arrestors, an important safety feature not standard on other watering systems. The internal flame arrestors prevent internal sparks from passing through the watering system to neighboring cells while the external flame arrestor prevents external sparks from entering the Trojan battery.

Snake™ or Clampless Tubing

The HydroLink system offers a patented Snake™ tubing assembly. This one-piece unit eliminates the need for multi connections resulting in fewer parts and quicker watering. HydroLink is also available with clampless tubing for customizable configurations.

Warranty

HydroLink™ watering system comes with a four-year, limited warranty.